



UKRHIMPLAST®

Ukraine, 07415, Kiev region, Zazimie, Radgospna str.3a Registration Code 33458437,

Tel/Fax:+38(044) 492-82-06, e-mail:info@ukrhimplast.com

www.ukrhimplast.com

ЕМКОСТИ ДЛЯ ВОДЫ, ПИЩЕВЫХ И ХИМИЧЕСКИХ ПРОДУКТОВ

Type	Volumе, l	Dimensions L/W/H (mm)	Neck diameter, mm	Thread, inch	Wall, mm	Weight, kg	Price grn. incl. VAT	Price grn. incl. VAT	
PLAIN, RECTANGULAR TANKS									
	SG - 100	100	800/480/340	220	3/4	3,5			
	SG - 200	200	1000/480/505	220	3/4	3,5			
	SG - 300	300	1230/600/525	220	3/4	4			
	SK - 200	200	785/610/566	350	3/4	3,5			
	SK - 300	300	1095/630/565	350	3/4	4			
	SK - 400	400	1265/670/627	350	3/4	4			
	SK - 500	500	1565/655/610	350	3/4	4			
	B - 1000	1000	1532/670/1306	350	1	5			
	B - 1500	1500	1724/766/1570	350	1	5,5			
	B - 2000	1900	2350/765/1437	350	1	6			
HORIZONTAL TANKS									
	G - 150	150	700/574/583	220	3/4	3,5			
	G - 250	250	1060/574/583	220	3/4	3,5			
	G - 350	350	920/768/781	200	3/4	4			
	G - 500	500	1100/850/830	350	3/4	4			
	G - 505	500	1320/812/733	350	3/4	4			
	G - 1000	1000	1500/1029/1029	350	3/4	4,5			
	G - 1500	1500	1500/1237/1234	400	1	4,5			
			//						
	G - 3000	3000	2350/1434/1280	350	1 1/4	5,5			
G - 5000	5000	2400/2000/1560	400		6,5				
SHOWER TANKS									
		140	900/900/287	220	1/2	4			
		200	1175//274	350	1/2	4,5			
VERTICAL TANKS									
	SV - 200-1	200	600/950	1092	3/4	3,5	7		
	V - 100	100	480/650	220	3/4	3,5			
	V - 250	250	600/1091	220	3/4	3,5			
	V - 320	320	600/1390	220	3/4	3,5			
	V - 300	300	710/877	350	3/4	3,5			
	V - 350	350	744/980	350	3/4	3,5			
	V - 500	500	830/1075	350	3/4	4			
	V - 505	500	740/1440	350	3/4	4			
	V - 990	990	740/2550	350	1	5			
	V - 1000	1000	1030/1400	350	3/4	4,5			
	V - 2000	2000	1230/2000	7487	1	4,5			
	V - 3000	3000	1630/1600	400	1 1/4	6			
	V - 5000	5000	1850/2100	400	1 1/4	6			
			/		-				
V - 8000	8000	2230/2522	640	-	8	255			
V - 10000	10000	2400/2728	400	-	7,5				

Material: made of polyethylene, resistant to UV, product exposure does not alter the physical and chemical properties in the temperature range from -40 ° C to +60 ° C.


Color: regular- blue.

Connection: tanks on the side (top and bottom) have a threaded holes.

TANKS FOR TRANSPORTATION

Tanks are intended for the transportation of non-hazardous liquids.

They are equipped with an air valve caps. The increased weight of products, compared with conventional tanks, provides additional wall thickness (8-10 mm). Material of tanks has high strength and resistance to dynamic loads.

Type		Volume, l	Dimensions L/W/H (mm)	Neck diameter, mm	Wall, mm	Weigh t, kg	Price GRN. incl. VAT	Price GRN. incl. VAT
	G - 1000E	1000*	1500/1030/1030	350	6			
	G - 1500E	1500*	1500/1230/1230	400	6			
	G - 2000E	2000*	2130/1200/1250	400	6.5			
	G - 3000E	3000*	2320/1440/1280	350	7			
	G - 5000 АГРО	5000*	2470/1784/1850	400	10			

When installed on a vehicle body, tank should be secured with straps and stops that prevent displacement of the vessel in motion should be ensured.

Tanks for sprayers and machinery should be installed and assembled according to the technical documentation of the manufacturer of the equipment.

Tanks are made of high-strength, freeze-resistant (from -40 ° C to +60 ° C) polyethylene. The material of products is durable and resistant to UV exposure.



WE DEVELOPE PRODUCTS, BASED ON CUSTOMER DRAWINGS!