



www.ukrhimplast.com

UKRHIMPLAST®

Ukraine, 07415, Kiev region, Zazimie, Radgospna str.3a Registration Code 33458437,

Tel/Fax:+38(044) 492-82-06, e-mail:info@ukrhimplast.com

www.ukrhimplast.com

ЕМКОСТИ ДЛЯ ВОДЫ, ПИЩЕВЫХ И ХИМИЧЕСКИХ ПРОДУКТОВ

| Type | Volumе, l | Dimensions L/W/H (mm) | Neck diameter, mm | Thread, inch | Wall, mm | Weight, kg | Price grn. incl. VAT | Price grn. incl. VAT | |
|---------------------------------|-------------------|-----------------------|-------------------|--------------|----------|------------|----------------------|----------------------|--|
| PLAIN, RECTANGULAR TANKS | | | | | | | | | |
| | SG - 100 | 100 | 800/480/340 | 220 | 3/4 | 3,5 | | | |
| | SG - 200 | 200 | 1000/480/505 | 220 | 3/4 | 3,5 | | | |
| | SG - 300 | 300 | 1230/600/525 | 220 | 3/4 | 4 | | | |
| | SK - 200 | 200 | 785/610/566 | 350 | 3/4 | 3,5 | | | |
| | SK - 300 | 300 | 1095/630/565 | 350 | 3/4 | 4 | | | |
| | SK - 400 | 400 | 1265/670/627 | 350 | 3/4 | 4 | | | |
| | SK - 500 | 500 | 1565/655/610 | 350 | 3/4 | 4 | | | |
| | B - 1000 | 1000 | 1532/670/1306 | 350 | 3/4 | 5 | | | |
| | B - 1500 | 1500 | 1724/766/1570 | 350 | 1 | 5,5 | | | |
| | B - 2000 | 1900 | 2350/765/1437 | 350 | 1 | 6 | | | |
| HORIZONTAL TANKS | | | | | | | | | |
| | G - 150 | 150 | 700/574/583 | 220 | 3/4 | 3,5 | | | |
| | G - 250 | 250 | 1060/574/583 | 220 | 3/4 | 3,5 | | | |
| | G - 350 | 350 | 920/768/781 | 200 | 3/4 | 4 | | | |
| | G - 500 | 500 | 1100/850/830 | 350 | 3/4 | 4 | | | |
| | G - 505 | 500 | 1320/812/733 | 350 | 3/4 | 4 | | | |
| | G - 1000 | 1000 | 1500/1029/1029 | 350 | 3/4 | 4,5 | | | |
| | G - 1500 | 1500 | 1500/1237/1234 | 400 | 1 | 4,5 | | | |
| | | | // | | | | | | |
| | G - 3000 | 3000 | 2350/1434/1280 | 350 | 1 1/4 | 5,5 | | | |
| | | // | | | | | | | |
| SHOWER TANKS | | | | | | | | | |
| | | 140 | 900/900/287 | 220 | 1/2 | 4 | | | |
| | | 200 | 1175//274 | 350 | 1/2 | 4,5 | | | |
| VERTICAL TANKS | | | | | | | | | |
| | SV - 200-1 | 200 | 600/950 | 1092 | 3/4 | 3,5 | 7 | | |
| | V - 100 | 100 | 480/650 | 220 | 3/4 | 3,5 | | | |
| | V - 250 | 250 | 600/1091 | 220 | 3/4 | 3,5 | | | |
| | V - 320 | 320 | 600/1390 | 220 | 3/4 | 3,5 | | | |
| | V - 300 | 300 | 710/877 | 350 | 3/4 | 3,5 | | | |
| | V - 350 | 350 | 744/980 | 350 | 3/4 | 3,5 | | | |
| | V - 500 | 500 | 830/1075 | 350 | 3/4 | 4 | | | |
| | V - 505 | 500 | 740/1440 | 350 | 3/4 | 4 | | | |
| | V - 990 | 990 | 740/2550 | 350 | 1 | 5 | | | |
| | V - 1000 | 1000 | 1030/1400 | 350 | 3/4 | 4,5 | | | |
| | V - 2000 | 2000 | 1230/2000 | 11096 | 3/4 | 4,5 | | | |
| | V - 3000 | 3000 | 1630/1600 | 400 | 1 1/4 | 6 | | | |
| | V - 5000 | 5000 | 1850/2100 | 400 | 1 1/4 | 6 | | | |
| | | | / | | - | | | | |
| | V - 8000 | 8000 | 2230/2522 | 640 | - | 8 | 255 | | |
| V - 10000 | 10000 | 2400/2728 | 400 | - | 7,5 | | | | |

Material: made of polyethylene, resistant to UV, product exposure does not alter the physical and chemical properties in the temperature range from -40 ° C to +60 ° C.


Color: regular- blue.

Connection: tanks on the side (top and bottom) have a threaded holes.

TANKS FOR TRANSPORTATION

Tanks are intended for the transportation of non-hazardous liquids.

They are equipped with an air valve caps. The increased weight of products, compared with conventional tanks, provides additional wall thickness (8-10 mm). Material of tanks has high strength and resistance to dynamic loads.

| Type | | Volume, l | Dimensions L/W/H (mm) | Neck diameter, mm | Wall, mm | Weight, kg | Price GRN. incl. VAT | Price GRN. incl. VAT |
|---|----------------------|--------------|--------------------------|-------------------------|-------------|---------------|-------------------------------|-------------------------------|
|  | G - 1000E | 1000* | 1500/1030/1030 | 350 | 6 | | | |
| | G - 1500E | 1500* | 1500/1230/1230 | 400 | 6 | | | |
| | G - 2000E | 2000* | 2130/1200/1250 | 400 | 6.5 | | | |
| | G - 3000E | 3000* | 2320/1440/1280 | 350 | 7 | | | |
| | G - 5000 АГРО | 5000* | 2470/1784/1850 | 400 | 10 | | | |

When installed on a vehicle body, tank should be secured with straps and stops that prevent displacement of the vessel in motion should be ensured.

Tanks for sprayers and machinery should be installed and assembled according to the technical documentation of the manufacturer of the equipment.

Tanks are made of high-strength, freeze-resistant (from -40 ° C to +60 ° C) polyethylene. The material of products is durable and resistant to UV exposure.



WE DEVELOPE PRODUCTS, BASED ON CUSTOMER DRAWINGS!