



# UKRHIMPLAST®

Ukraine, 07415, Kiev region, Zazimie, Radgospna str.3a Registration Code 33458437,

Tel/Fax:+38(044) 492-82-06, e-mail:[info@ukrhimplast.com](mailto:info@ukrhimplast.com)

[www.ukrhimplast.com](http://www.ukrhimplast.com)

## ЕМКОСТИ ДЛЯ ВОДЫ, ПИЩЕВЫХ И ХИМИЧЕСКИХ ПРОДУКТОВ

Type	Volumе, l	Dimensions L/W/H (mm)	Neck diameter, mm	Thread, inch	Wall, mm	Weight, kg	Price uah. incl. VAT	Price usd. incl. VAT	
<b>PLAIN, RECTANGULAR TANKS</b>									
	<b>SG - 100</b>	100	800/480/340	220	3/4	3,5	5	718,00	28,72
	<b>SG - 200</b>	200	1000/480/505	220	3/4	3,5	8	1 149,00	45,96
	<b>SG - 300</b>	300	1230/600/525	220	3/4	4	12	1 580,00	63,20
	<b>SK - 200</b>	200	785/610/566	350	3/4	3,5	8	1 149,00	45,96
	<b>SK - 300</b>	300	1095/630/565	350	3/4	4	12	1 580,00	63,20
	<b>SK - 400</b>	400	1265/670/627	350	3/4	4	16	2 155,00	86,20
	<b>SK - 500</b>	500	1565/655/610	350	3/4	4	19	2 442,00	97,68
	<b>B - 1000</b>	1000	1532/670/1306	350	1	5	34	5 027,00	201,08
			//						
<b>B - 2000</b>	1900	2350/765/1437	350	1	6	72	10 055,00	402,20	
<b>HORIZONTAL TANKS</b>									
	<b>G - 150</b>	150	700/574/583	220	3/4	3,5	6	718,00	28,72
	<b>G - 250</b>	250	1060/574/583	220	3/4	3,5	10	1 149,00	45,96
	<b>G - 350</b>	350	920/768/781	200	3/4	4	11	1 580,00	63,20
	<b>G - 500</b>	500	1100/850/830	350	3/4	4	18	2 586,00	103,44
	<b>G - 505</b>	500	1320/812/733	350	3/4	4	18	2 442,00	97,68
	<b>G - 1000</b>	1000	1500/1029/1029	350	1	4,5	30	4 309,00	172,36
	<b>G - 1500</b>	1500	1500/1237/1234	400	1	4,5	40	5 746,00	229,84
	<b>G - 2000</b>	2000	2130/1204/1189	284	1	5	60	7 900,00	316,00
	<b>G - 3000</b>	3000	2350/1434/1280	350	1 1/4	5,5	80	12 928,00	517,12
	<b>G - 5000</b>	5000	2400/2000/1560	400		6.5		14 900,00	596,00
<b>SHOWER TANKS</b>									
		140	900/900/236	220	1/2	4	7	862,00	34,48
		200	1175//274	350	1/2	4,5	12	1 580,00	63,20
<b>VERTICAL TANKS</b>									
	<b>SV - 200-1</b>	200	600/950	100	3/4	3.5	7	not in stock	not in stock
	<b>V - 100</b>	100	480/650	200	3/4	3,5	4	575,00	23,00
	<b>V - 250</b>	250	600/1091	220	3/4	3,5	8	1 149,00	45,96
	<b>V - 320</b>	320	600/1390	220	3/4	3,5	10	1 436,00	57,44
	<b>V - 300</b>	300	710/877	350	3/4	3,5	10	1 436,00	57,44
	<b>V - 350</b>	350	744/980	350	3/4	3,5	10	1 436,00	57,44
	<b>V - 500</b>	500	830/1075	350	3/4	4	16	2 298,00	91,92
	<b>V - 505</b>	505	740/1440	350	3/4	4	16	2 298,00	91,92
	<b>V - 990</b>	990	740/2550	350	1	5	28	4 022,00	160,88
	<b>V - 1000</b>	1000	1030/1400	400	1	4,5	28	3 591,00	143,64
	<b>V - 2000</b>	2000	1230/2000	400	1	4,5	50	6 646,00	265,84
	<b>V - 3000</b>	3000	1630/1600	400	1 1/4	5	80	10 773,00	430,92
	<b>V - 5000</b>	5000	1850/2100	400	1 1/4	6	110	14 364,00	574,56

			/		-				
	<b>V - 8000</b>	8000	2230/2522	640	-	8	255	<i>not in stock</i>	<i>not in stock</i>
	<b>V - 10000</b>	10000	2400/2728	400	-	7,5	304	<b>34</b> <b>474,00</b>	<b>1</b> <b>378,96</b>

**Material:** made of polyethylene, resistant to UV, product exposure does not alter the physical and chemical properties in the temperature range from -40 ° C to +60 ° C.


**Color:** regular- blue.

**Connection:** tanks on the side (top and bottom) have a threaded holes.

## TANKS FOR TRANSPORTATION

Tanks are intended for the transportation of non-hazardous liquids.

They are equipped with an air valve caps. The increased weight of products, compared with conventional tanks, provides additional wall thickness (8-10 mm). Material of tanks has high strength and resistance to dynamic loads.

Type		Volume, l	Dimensions L/W/H (mm)	Neck diameter, mm	Wall, mm	Weight, kg	Price UAH. incl. VAT	Price USD. incl. VAT
	<b>G - 1000E</b>	1000*	1500/1030/1030	350	6	36	5 186,0 0	207,4 4
	<b>G - 1500E</b>	1500*	1500/1230/1230	400	6	54	7 779,0 0	311,1 6
	<b>G - 2000E</b>	2000*	2130/1200/1250	400	6.5	70	9 075,0 0	363,0 0
	<b>G - 3000E</b>	3000*	2320/1440/1280	350	7	120	14 909,00	596,36
	<b>G - 5000 АГРО</b>	5000*	2470/1784/1850	400	10	205	23 889,00	955,56

When installed on a vehicle body, tank should be secured with straps and stops that prevent displacement of the vessel in motion should be ensured.

Tanks for sprayers and machinery should be installed and assembled according to the technical documentation of the manufacturer of the equipment.

*Tanks are made of high-strength, freeze-resistant (from -40 ° C to +60 ° C) polyethylene. The material of products is durable and resistant to UV exposure.*



**WE DEVELOPE PRODUCTS, BASED ON CUSTOMER DRAWINGS!**